


Switchcraft®

NEW
PRODUCT
BULLETIN

PD SERIES RECEPTACLES WITH SOLDER CUPS



PD3MS1
3-pin male,
straight (rear exit)
PC terminals.
Front mount.

PD3MRML2
3-pin male, right
angle (bottom exit)
long screw machine
terminals. Panel
mount holes not
countersunk.

PD3FRL1
3-contact female,
right-angle (left exit)
PC/solder terminals.
Ground lug. Front
panel mount.

PD3FRA1
3-contact female,
right-angle (bottom
exit) PC/solder
terminals. Ground
lug. Front panel
mount.

Switchcraft now offers the PD Series with a solder cup option. This new option is perfect for panel mount, non-PC board applications. The solder cups offer a generous area to solder. Available in male and female, the receptacles can be mounted from the front or rear of the panel. See the back page for part numbers. This new option is in addition to all of the previous termination options available with the PD Series.

FEATURES AND BENEFITS

- 3 pins/contacts
- Male and female
- Straight or right-angle PC, and solder cups
- Front or rear panel mount
- Females feature large contact area for higher ratings and longer life
- Special PC/solder terminal type with exits at 0° (down), 90° (right), 180° (top), and 270° (left)
- Rugged molded black glass-filled thermoplastic housings
- Compatible with other Switchcraft Q-G® types


SPECIFICATIONS

Housing: Black molded thermoplastic, glass-filled.
Ground Pin: Copper alloy.
Stamped Terminals/Contacts: Copper alloy, electroplated.
Screw Machine Terminals/Pins: Copper alloy, silver-

BIFURCATED PC TERMINALS

Bifurcation configuration for PC terminals on selected connectors offers these advantages.

1. Provides convenient snap-in retention for mounting.
2. Holds connector securely to PCB during wavesoldering.
3. Adds strength to all terminal connections by solder "wicking" through PCB and up sides of terminals.




PD SERIES RECEPTACLES

Switchcraft®

PD SERIES PART NUMBERING SYSTEM

SERIES PD	PINS/ CONTACTS	GENDER	GENDER	HOUSING	TERMINALS	
P D	3	F - Female M - Male	FEMALE RA - Right-angle, Bottom Exit RL - Right-angle, Left exit RR - Right-angle, Right Exit RU - Right-angle, Top Exit RML - Right-angle, Bottom Exit, Long Screw Mach. Term. RMS - Right-angle, Bottom Exit, Short Screw Mach. Term. S - Straight, Rear Exit SC - Solder Cup	MALE RML - Right-angle, Bottom Exit, Long Screw Mach. Term. RMS - Right-angle, Bottom Exit, Short Screw Mach. Term. S - Straight, Rear Exit SC - Solder Cup	1 - Front Mount .11 inches (2.8 mm) diameter flange mounting holes 2 - Rear Mount .091 inches (2.3 mm) diameter flange mounting holes 3 - Front Mount .126 inches (3.2 mm) diameter flange mounting holes	Blank = Silver terminals AU = Gold terminals



NOTE: Contact your Switchcraft Representative for price and delivery.

PD SERIES RECEPTACLES

Switchcraft®

Switchcraft, Inc. is a major manufacturer of a broad line of electronic/electromechanical components for the audio/video, telecommunication, data communication, computer, medical, military, appliance, transportation and instrumentation markets.

SWITCHCRAFT, INC.
5555 North Elston Avenue
Chicago, IL 60630
773-792-2700
Fax 773-792-2129
www.switchcraft.com

Switchcraft® — Consistently Excellent Since

We reserve the right to change the prices, specifications and/or part numbers contained herein when circumstances make it necessary.

Form No. GL-2200 3/98

© Switchcraft, Inc. 1998

Printed in U.S.A.

