ASSY P/N CABLE O.D. 13382-10SG-321 | 0.21-0.25 [5.3-6.3mm] 13382-10SG-326 0.26-0.30 [6.6-7.6mm] 13382-10SG-331 | 0.31-0.38 [7.8-9.6mm] ALL PARTS TO BE BULK PACKED.

CONTACTS TO BE INSERT INTO CONNECTOR.

SEE DRAWING HPMXSTD FOR HOLE PATTERN (2) #4 x 3/8 SCREW-SELF TAPPING MAT'L: STAINLESS STEEL -BACK STRAP MAT'L: THERMOPLASTIC, BLACK -(10) #16 SOCKET CONTACTS SOLDER TAIL MAT'L: GOLD PLATED, COPPER ALLOY **CUSTOMER PRINT** 0.930 ± 0.010 0.985 ±0.015 0.452 ± 0.010 → 0.985 REF. → [23.6mm] 0.040 REF. -[25.0mm] [25.0mm] **KEYWAY** [11.5mm] [1.0mm] 0.049 ± 0.015 [1.2mm] **MATING FACE** BACKSHELL − 1.280 ±0.015 --- MAT'L: THERMOPLASTIC, BLACK O-RING-MAT'L: RUBBER, BLACK [32.5mm] -COUPLING RING MAT'L: THERMOPLASTIC, BLACK CABLE CONNECTOR, FEMALE MAT'L: THERMOPLASTIC, BLACK -GROMMET MAT'L: RUBBER, BLACK FOR CABLE O.D. SEE TABLE 13382-10SG-3XX 2.538 REF. [64.5mm] 1.980 REF 50.3mm] **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, 1.049 [26.6mm] DISCLOSURE, OR USE OF THIS
DOCUMENT /INFORMATION IS EXPRESSLY
PROHIBITED UNLESS AUTHORIZED IN DRAWING CREATED PER DOR 14-E149SL #35 AN 10-02-14 WRITING BY CONXALL CORPORATION. REV. INIT. DATE DESCRIPTION 3. DRAWN BY: DATE: 10-02-14 CHECKED BY =onxal DUPLICATION OR DISTRIBUTION
THIS DOCUMENT IS PROHIBITED APPROVED BY: _ SHOWN ASSEMBLED KIT FOR CUSTOMER REFERENCE ONLY 601 E. WILDWOOD VILLA PARK, IL 60181 DATE: ITLE: CONNECTOR KIT
(10) #16 SOCKET CONTACTS, SOLDER
MAXI-CON-X
USTOMER: STANDARD PRODUCT SCALE NTS SHEET 1 OF 1 DIMENSIONS IN BRACKETS [] ARE METRIC. **ROHS COMPLIANT** PART NUMBER: 13382-10SG-3XX