



NOTES:

- MATERIALS:  
 HANDLE & LOCKRING - COPPER ALLOY, NICKEL PLATED  
 TIP ROD, SLEEVE & PLUG BODY - COPPER ALLOY, NICKEL PLATED  
 TERMINALS - COPPER ALLOY, TIN PLATED  
 INSULATORS - PHENOLIC, MYLAR & THERMOPLASTIC
- THIS PRODUCT IS RoHS COMPLIANT.

SECTION **A-A**

CUSTOMER DRAWING

				★ STAR SYMBOL DENOTES CRITICAL DIMENSION	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
				UNLESS OTHERWISE SPECIFIED	SIZE	WIDTH	MULT	LBS/M	TEMPER
				1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.01 - THREE PLACE DECIMALS ±0.005 - ANGLES ±1° - ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.	FINISH			MATERIAL	
				2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002	SPEC No.			SPEC No.	
				3. REMOVE ALL BURRS	FIRST USED ON		SCALE		<b>Switchcraft®</b>
					DATE DRAWN		2:1		
D	23253	2-16-00	TO	TJK	30-Mar-16	BY TO	CHKD TO	APVD TJK	
							3-30-16	3-30-16	SHEET   OF
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.	REV
					PLUG ASSEMBLY			298	D
					3 CONDUCTOR LOCKING, RoHS				