



NOTES:

1. MATERIALS:  
 3 CONDUCTOR PHONE PLUG ASSEMBLY:  
 PLUG - COPPER ALLOY, NICKEL PLATED  
 INSULATORS - PHENOLIC, MYLAR & THERMOPLASTIC  
 ADAPTER HOUSING - ZINC ALLOY, NICKEL PLATED  
 TUBULAR INSULATOR - MYLAR  
 SCREWS - STEEL, NICKEL PLATED

- FEMALE XLR SUB-ASSEMBLY:  
 SHELL - STAINLESS STEEL  
 INSULATORS - THERMOPLASTIC, GREEN  
 CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED  
 LATCH - ZINC ALLOY, NICKEL PLATED  
 GROUND TERMINAL - COPPER ALLOY, TIN PLATED  
 SCREW - STAINLESS STEEL

2. SHIPPED WIRED AND ASSEMBLED IN PLASTIC BAG.  
 3. THIS PRODUCT IS RoHS COMPLIANT.

FEMALE XLR SUB-ASSEMBLY	PHONE PLUG ASSEMBLY
PIN 1	SLEEVE
PIN 2	TIP
PIN 3	RING
GROUND TERMINAL JUMPERED TO PIN 1	SLEEVE

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
UNLESS OTHERWISE SPECIFIED  1. ALL DIMENSIONS IN INCHES [mm] - TWO PLACE DECIMALS ±0.02 [0.5] - THREE PLACE DECIMALS ±0.005 [0.13]					SIZE	WIDTH	MULT	LBS/M	TEMPER	
					FINISH SPEC No.				MATERIAL SPEC No.	
DO NOT SCALE DRAWING					FIRST USED ON *			SCALE 2:1		
					DATE DRAWN	BY	CHKD TO	APVD		
A	26204	1-20-07	TO	TJK	12-1-15	TO	12-1-15	TJK		
REV	ECO NUMBER	DATE	BY	APVD	NAME ADAPTER, FEMALE 3 PIN XLR TO 3 CONDUCTOR PLUG, WIRED, RoHS				PART No.	REV
REVISIONS					386AWX				A	

