

# NOTES:

## 1. MATERIALS:

### 3 CONDUCTOR PHONE PLUG ASSEMBLY:

PLUG - COPPER ALLOY, NICKEL PLATED  
INSULATORS - PHENOLIC, MYLAR & THERMOPLASTIC  
ADAPTER HOUSING - ZINC ALLOY, NICKEL PLATED  
TUBULAR INSULATOR - MYLAR  
SCREWS - STEEL, NICKEL PLATED

### MALE XLR SUB-ASSEMBLY:


SHELL - STAINLESS STEEL  
INSULATORS - THERMOPLASTIC, GREEN  
CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED  
LATCH - ZINC ALLOY, NICKEL PLATED  
GROUND TERMINAL - COPPER ALLOY, TIN PLATED  
SCREW - STAINLESS STEEL

## 2. SHIPPED WIRED AND ASSEMBLED IN PLASTIC BAG.

## 3. THIS PRODUCT IS RoHS COMPLIANT.

MALE XLR SUB-ASSEMBLY	PHONE PLUG ASSEMBLY
PIN 1	SLEEVE
PIN 2	TIP
PIN 3	RING
GROUND TERMINAL JUMPED TO PIN 1	SLEEVE

**CUSTOMER DRAWING**

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.											
					UNLESS OTHERWISE SPECIFIED  1. ALL DIMENSIONS IN INCHES [mm]  - TWO PLACE DECIMALS    ±0.02    [0.5]  - THREE PLACE DECIMALS    ±0.005    [0.13]	SIZE		WIDTH		MULT		LBS/M		TEMPER			
						FINISH SPEC No.						MATERIAL SPEC No.					
						FIRST USED ON *				SCALE 1:1							
						DATE DRAWN 12-1-15		BY TO	CHKD TO 12-1-15		APVD TJK 12-1-15						
A	26204	1-20-07	TO	TJK		SHEET    1                      OF                      1											
REV	ECO NUMBER	DATE	BY	APVD													
REVISIONS					DO NOT SCALE DRAWING	NAME    ADAPTER, MALE 3 PIN XLR TO 3 CONDUCTOR PLUG, WIRED, RoHS						PART No.                      387AWX				REV A	

SolidWorks CAD File

