



- NOTES:
1. KNOB AND HARDWARE SHIPPED UNASSEMBLED.
 2. MAX PANEL THICKNESS: 0.25 [6.4]
 3. MATERIALS:
 FRAME - CRS, ZINC PLATED
 BUSHING & ACTUATOR - COPPER ALLOY, NICKEL PLATED
 SPRINGS - SPECIAL COPPER ALLOY
 TERMINALS - TINNED DIPPED SOLDER LUGS
 INSULATORS - PHENOLIC
 LIFTERS & ROLLERS - THERMOPLASTIC
 SCREWS - CRS, NICKEL PLATED
 HEX NUT - COPPER ALLOY, NICKEL PLATED
 WASHER - CRS, NICKEL PLATED
 KNOB - THERMOPLASTIC, BLACK
 4. THIS PRODUCT IS RoHS COMPLIANT

CUSTOMER DRAWING

REV	ECO NUMBER	DATE	BY	APVD
A	27887	05-12-17	PC	TJK
REVISIONS				

★ STAR SYMBOL DENOTES CRITICAL DIMENSION

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES
 - TWO PLACE DECIMALS ±0.01
 - THREE PLACE DECIMALS ±0.005
 - ANGLES ±1°
 - ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.
2. FEATURES ON THE SAME CENTERLINE
 MUST BE ALIGNED WITHIN ±0.002
3. REMOVE ALL BURRS

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE		WIDTH		MULT		LBS/M		TEMPER	
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON				SCALE					
				2:1					
DATE DRAWN	BY	CHKD	APVD	Switchcraft [®]					
May-14-19	PC	PC	TJK						
NAME				PART No.		REV			
LT SERIES LEVER SWITCH				41206LX		A			
2 POSITION LOCKING, RoHS									