

1. DIMENSIONS SHOWN FOR REFERENCE ONLY.

 \rightarrow

- 2. HEX NUT AND FLAT WASHER SUPPLIED UNASSEMBLED.
- 3. MATERIAL:
 HOUSING, HEX NUT COPPER ALLOY, NICKEL PLATED
 INSULATOR HOUSING THERMOPLASTIC, RED
 TERMINAL INSULATORS PHENOLIC
 FLAT WASHER STEEL, NICKEL PLATED
 PIN, SPRING, TERMINALS COPPER ALLOY, SILVER PLATED
- (B) 4. IT IS RECOMMENDED THAT THE JACK MOUNTING NUT BE TIGHTENED SNUG BY HAND BEFORE APPLYING A FINAL TIGHTENING TORQUE OF 8-10 LB-IN USING HAND TOOLS ONLY. POWER DRIVER OR IMPACT DRIVERS ARE NOT RECOMMENDED.
 - 5. THESE PRODUCTS ARE RoHS COMPLIANT

CUSTOMER DRAWING

| | | | | | _ | - | | | | | | | | | | |
|---|-----------|------------|--------------|----|------|--------------------------------------|-------------------|------|----------|--|--------------|-------|---|------|-----|----------|
| | | | | | | | | | | OPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED IDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | |
| | | | | | | UNLESS OTHERWISE SPECIFIED | SIZE | v | VIDTH | MULT | | LBS/M | | TEMI | PER | |
| | | | | | | 1. ALL DIMENSIONS IN INCHES [mm] | FINISH | | | | MATERIAL | | | | | |
| | | | | | | - TWO PLACE DECIMALS ±0.02 [0.5] | SPEC No. | | | | SPEC No. | | | | | |
| | | | | | | - THREE PLACE DECIMALS ±0.005 [0.13] | FIRST USED ON | | N | SCALE 3:1 | -Swifeheraff | | | | | |
| | В | 28397 | 06/11/21 | PC | TJK | | DATE DRAWN | BY | CHKD | APVD | | | | | | <u>↓</u> |
| ŀ | | | 0.4.10.0.4.0 | | | | 02/06/17 F | PNK | PNK | SRC | | | | | | |
| - | Α | 27987 | 01/08/18 | PC | TJK | | 02/00/17 | 1 | 02/06/17 | 02/06/17 | | SHEET | 1 | OF | 1 | |
| | REV | ECO NUMBER | DATE | BY | APVD | | NAME 2.1 | mm P | OWER JAC | KS | PART No. | | | _ | | REV |
| | REVISIONS | | | | | DO NOT SCALE DRAWING | SOLDER LUGS, RoHS | | | | 721A [| | | | В | |