CA168804P03990 CA168804P07990 FINISHED CABLE ASSEMBLY 3 FEET OR SHORTER TO BE BUNDLED.
FINISHED CABLE ASSEMBLY OVER 3 FEET TO BE COILED
OVERMOLD BOOT MATERIAL: PVC, BLACK
ELECTRICAL TEST: 100% CONTINUITY CA168804P19790 CA168804P39490 CA168804PXXX90 ALL DIMENSIONS ARE REFERENCE ONLY EXCEPT WHEN NOTED WITH **TOLERANCE** "X" DIM. CUSTOMER PRINT O-RING-MAT'L: RUBBER, BLACK - 2.030 IN. [51.6mm] MASTER KEY CUT BLUNT END "A" CABLE STRAIGHT FLEX OVERMOLDED CABLE CONNECTOR, MALE FACE VIEW (4)-#22 AWG CONDUCTORS JACKET: PVC, BLACK MAT'L: NYLON, BLACK 0.195 O.D. REF. (4) #22 PIN CONTACTS 300 V MÁT'L: GOLD PLATED COPPER ALLOY COUPLING RING OIL RESISTANT CXA #16880-4PG MAT'L: NYLON, BLACK CA168804PXXX90 **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL ΑN 03-18-21 CHANGED TO FLEX OVERMOLD, UPDATED CONN. DIM. PER ECR 9574 CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS AN 09-16-19 DRAWING CREATED PER DOR 19-SQ104237JS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN REV. INIT. DATE DESCRIPTION WRITING BY CONXALL CORPORATION. 08-21-19 AN APPROVED BY: \_ 601 E. WILDWOOD VILLA PARK, IL 60181 DATE: \_ CABLE ASSEMBLY WIRE COLOR CODE, END "A" (4) #22 PIN CONTACTS

DIMENSIONS IN BRACKET [ ] ARE METRIC.

POS. 1 POS. 2 POS. 3 POS. 4

BLU

BRN

ASS'Y P/N "X" DIM. 3 FT. 3 1/2 IN. ± 2 IN. [1M] 6 FT. 7 IN. ± 2 IN. [2M] 16 FT. 5 IN. ± 4 IN. [5M] 32 FT. 9 3/4 IN. ± 8 IN. [10M]

-CABLE LENGTH IN "INCHES"

MICRO-CON-X, STRAIGHT STANDARD PRODUCT

PART NUMBER: CA168804PXXX90

SCALE NTS

**ROHS COMPLIANT** 

SHEET 1 OF 1