ASS'Y P/N "X" DIM. 3 FT. 3 1/2 IN. ± 2 IN. [1M] CA168804S03990 CA168804S07990 6 FT. 7 IN. ± 2 IN. [2M] FINISHED CABLE ASSEMBLY 3 FEET OR SHORTER TO BE BUNDLED.
 FINISHED CABLE ASSEMBLY OVER 3 FEET TO BE COILED.
 OVERMOLD BOOT MATERIAL: PVC, BLACK
 ELECTRICAL TEST: 100% CONTINUITY CA168804S19790 16 FT. 5 IN. ± 4 IN. [5M] CA168804S39490 32 FT. 9 3/4 IN. ± 8 IN. [10M] CA168804SXXX90 ALL DIMENSIONS ARE REFERENCE ONLY EXCEPT WHEN NOTED WITH **TOLERANCE** -CABLE LENGTH IN "INCHES" CUSTOMER PRINT "X" DIM. O-RING-MAT'L: RUBBER, BLACK 2.030 IN. [51.6mm] MASTER **KEYWAY** $\langle B \rangle$ JAWAW CUT BLUNT (4)-#22 AWG CONDUCTORS JACKET: PVC, BLACK STRAIGHT FLEX OVERMOLDED CABLE CONNECTOR, FEMALE MAT'L: NYLON, BLACK
(4) #22 SOCKET CONTACTS
MAT'L: GOLD PLATED COPPER ALLOY 0.195 O.D. REF. COUPLING RING 300 V MAT'L: NYLON, BLACK OIL RESISTANT CXA #16880-4SG CA168804SXXX90 **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL AN 03-18-21 CHANGED TO FLEX OVERMOLD, UPDATED CONN. DIM. PER ECR 9574 CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS AN 09-16-19 DRAWING CREATED PER DOR 19-SQ104237JS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN REV. INIT. DATE DESCRIPTION WRITING BY CONXALL CORPORATION. 08-20-19 AN APPROVED BY: _ 601 E. WILDWOOD VILLA PARK, IL 60181 DATE: _ CABLE ASSEMBLY WIRE COLOR CODE, END "A" (4) #22 SOCKET CONTACTS MICRO-CON-X, STRAIGHT STANDARD PRODUCT POS. 1 POS. 2 POS. 3 POS. 4 SCALE NTS SHEET 1 OF 1 DIMENSIONS IN BRACKET [] ARE METRIC. **ROHS COMPLIANT** BRN PART NUMBER: CA168804SXXX90