

EN3 Cable Assembly

Cable: 2/20 AWG black cable, 0.215" dia ref

Length: 32 ft 9 11/16 in (10 m)



End A: straight overmolded connector, black thermoplastic

Female socket contacts, gold plated copper alloy

End B: straight overmolded connector, black thermoplastic

Male pin contacts, gold plated copper alloy

EN3C2F



Cable Specifications

Wire Gauge: 20AWG

Conductor Stranding: 26X34 TC

Conductor Insulation: 15 Mils PVC/ AWM Style 1569

Insulation OD: 0.068" (1.73mm)

Conductor OD: 0.036" (0.91mm)

Jacket Material: 30 mils pressurized PVC, black

Temperature Rating: -30°C to 105°C

Power Rating: 300V

UL Recognized, CSA Certified and RoHS Compliant

Outer Jacket is UV and Water Resistant

Tissue Paper Separator

No Poly Filler, Unshielded

Pin No.	1	2
Wire Color	Black	Red

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

DRAWING GENERATED ONLINE BY
SWITCHCRAFT WEB CONFIGURATOR

ALL DIMENSIONS IN INCHES (MM)
UNLESS OTHERWISE SPECIFIED

Switchcraft
CONXALL

DRAWING IS NOT TO SCALE

SHEET 1 OF 1

PART No.

CAEN3C2F394DM - EN3 Cable Assembly

REV