






EN2C3FRA




## Cable Specifications

Wire Gauge: 20AWG  
 Conductor Stranding: 26X34 TC  
 Conductor Insulation: 15 Mils PVC/ AWM Style 1569  
 Insulation OD: 0.068" (1.73mm)  
 Conductor OD: 0.036" (0.91mm)  
 Jacket Material: 30 mils pressurized PVC, black  
 Temperature Rating: -30°C to 105°C  
 Power Rating: 300V

UL Recognized, CSA Certified and RoHS Compliant  
 Outer Jacket is UV and Water Resistant  
 Tissue Paper Separator  
 No Poly Filler, Unshielded

| Pin No.    | 1     | 2   | 3     |
|------------|-------|-----|-------|
| Wire Color | Black | Red | Green |

POLARIZATION KEY  
 STANDARD = 6 O'CLOCK



THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

DRAWING GENERATED ONLINE BY  
 SWITCHCRAFT WEB CONFIGURATOR

ALL DIMENSIONS IN INCHES (MM)  
 UNLESS OTHERWISE SPECIFIED

**Switchcraft**  
**CONXALL**

DRAWING IS NOT TO SCALE

SHEET 1 OF 1

PART No.

CARAEN2C3F079DF - EN2 Cable Assembly

REV