







EN2C3FRA



POLARIZATION KEY
STANDARD = 6 O'CLOCK



Cable Specifications

Wire Gauge: 20AWG
Conductor Stranding: 26X34 TC
Conductor Insulation: 15 Mils PVC/ AWM Style 1569
Insulation OD: 0.068" (1.73mm)
Conductor OD: 0.036" (0.91mm)
Jacket Material: 30 mils pressurized PVC, black
Temperature Rating: -30°C to 105°C
Power Rating: 300V

UL Recognized, CSA Certified and RoHS Compliant
Outer Jacket is UV and Water Resistant
Tissue Paper Separator
No Poly Filler, Unshielded

Pin No.	1	2	3
Wire Color	Black	Red	Green

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

DRAWING GENERATED ONLINE BY
SWITCHCRAFT WEB CONFIGURATOR

ALL DIMENSIONS IN INCHES (MM)
UNLESS OTHERWISE SPECIFIED

Switchcraft
CONXALL

DRAWING IS NOT TO SCALE

SHEET 1 OF 1

PART No.

CARAEN2C3F197DM - EN2 Cable Assembly

REV