



**NOTES:**

**1. MATERIALS:**

- BARREL, SHELL - BRASS ALLOY, NICKEL PLATED
- MICRO CONTACT - BRASS ALLOY, GOLD PLATED
- BNC CONTACT - BERYLLIUM COPPER, GOLD PLATED
- INSULATORS - TEFLON

2. CHARACTERISTIC IMPEDANCE: 75 Ohms.

3. MEETS SMPTE ST 2082-1 SPEC; BANDWIDTH: 12 GHz.

4. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					UNLESS OTHERWISE SPECIFIED			FINISH	
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL	
					- TWO PLACE DECIMALS ±0.02 [0.5]			SPEC No.	
					- THREE PLACE DECIMALS ±0.005 [0.13]			SCALE	
					FIRST USED ON			2:1	
					DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>
					8/4/21	MS	MS	TJK	
					NAME			PART No.	
					ADAPTER,			VMMPBNCF	
					BNC TO MICRO WECO, SHORT			REV	
					DO NOT SCALE DRAWING			A	
REV	ECO NUMBER	DATE	BY	APVD					
A	28476	05/10/22	PC	TJK					
REVISIONS									

