

BARREL, BODY - BRASS ALLOY, NICKEL PLATED CONTACT - BERYLLIUM COPPER, GOLD PLATED INSULATORS - TEFLON

- 2. CHARACTERISTIC IMPEDANCE: 75 Ohms.
- 3. MEETS SMPTE ST 2082-1 SPEC; BANDWITH: 12 GHz.
- 4. THIS PRODUCT IS RoHS COMPLIANT.

## **CUSTOMER DRAWING**

					UNLESS OTHERWISE SPECIFIED		HCRAFT		CONSIDERED PROPASED ON A CONFID			ICATION PUR	D MANUFACTURED URPOSES ONLY.	
					ALL DIMENSIONS IN INCHES [mm]     TWO PLACE DECIMALS ±0.02 [0.5]	FINISH SPEC No.				MATERIAL SPEC No.				
					- THREE PLACE DECIMALS ±0.005 [0.13]	FIRST USE		CHKD <b>MS</b>	SCALE 3:1 APVD TJK	Su	yila	e DC	Fa	
Α	28476	05/10/22	PC	TJK		8/4/21	MS	8/4/21	08/04/22		SHEET	1 (	OF 1	
REV	ECO NUMBER	DATE	BY	APVD		NAME MICPO B		DAPTER,		PART No.				REV
REVISIONS					DO NOT SCALE DRAWING	MICRO BNC TO MICRO WECO			VMMPMBF			A		

SolidWorks CAD File

