



NOTES:

- MEETS SMPTE 2082-1  
CHARACTERISTIC IMPEDANCE: 75 OHMS  
CONTACT RESISTANCE: LESS THAN 50 MILLIOHMS
- MATERIAL:  
PLUG BARREL: COPPER ALLOY, NICKEL PLATED (B)  
PLUG HANDLE: COPPER ALLOY, NICKEL PLATED  
CONTACT: COPPER ALLOY, GOLD PLATED (B)  
INSULATORS: TEFLON
- THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					UNLESS OTHERWISE SPECIFIED	SIZE	WIDTH	MULT	LBS/M	TEMPER
					1. ALL DIMENSIONS IN INCHES [mm]	FINISH			MATERIAL	
					- TWO PLACE DECIMALS $\pm 0.02$ [0.5]	SPEC No.			SPEC No.	
					- THREE PLACE DECIMALS $\pm 0.005$ [0.13]	FIRST USED ON		SCALE 2:1		
B	28606	6/20/23	TJK	TJK	DO NOT SCALE DRAWING	DATE DRAWN	BY	CHKD	APVD	
A	28195	08/29/19	PC	TJK		5/01/17	PNK	PNK	SRC	
REV	ECO NUMBER	DATE	BY	APVD		NAME	TERMINATING PLUG UHD SINGLE MICRO, RoHS			PART No.
REVISIONS									VMMSTPUHD	B