



- NOTES:
- 1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE :75 OHMS
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
 - 2. MATERIAL:
PLUG: COPPER ALLOY, NICKEL PLATED B
CONTACT: COPPER ALLOY, GOLD PLATED B
INSULATOR: TEFLON
OVERMOLD: THERMOPLASTIC ELASTOMER
 - 3. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES [mm]</div> <div>- TWO PLACE DECIMALS ±0.02 [0.5]</div> <div>- THREE PLACE DECIMALS ±0.005 [0.13]</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.													
						SIZE	WIDTH		MULT		LBS/M		TEMPER						
						FINISH SPEC No.						MATERIAL SPEC No.							
						FIRST USED ON				SCALE 3:2		Switchcraft®							
B	28606	6/20/23	TJK	TJK		DATE DRAWN	BY	CHKD		APVD									
A	28195	08/29/19	PC	TJK		5/01/17	PNK	PNK 5/01/17		SRC 5/01/17		SHEET 1 OF 1							
REV	ECO NUMBER	DATE	BY	APVD		NAME DUAL TERMINATED PLUG UHD MICRO, OVERMOLDED, RoHS						PART No. VMMTPUHD				REV B			
REVISIONS					DO NOT SCALE DRAWING														