NOTES:

1. FINISHED PRODUCT TO BE BOXED.
HEX NUTS AND GASKETS MAY BE PACKAGED SEPARATELY. CONTACTS ARE INSTALLED IN CO
 REAR WELL FILLED WITH EPOXY. CONTACTS ARE INSTALLED IN CONNECTOR. SEE DRAWING HPMUSTD FOR HOLE PATTERN
 ALL DIMENSIONS ARE FOR REFERENCE ONLY EXCEPT WHERE NOTED WITH TOLERANCE. .700 [17.8].550 .075 .745 [14]  $\lceil 1.9 \rceil$ [18.9] .153 FLAT (3) #12 PIN CONTACT PC TAIL STYLE MAT'L: COPPER ALLOY [1.3] 3.9 **→**.129±.015 KEY ▼ KEY 3.3±0.4 **EPOXY FILLED GOLD PLATED #12 CONTACT**  $\phi.058$ CUSTOMER PRINT  $\begin{bmatrix} 1.47 \\ 1.42 \end{bmatrix}$ 1.000  $\emptyset$ .980 [25.4] 24.9 **FLATS**  $\phi.021 \atop .019$  $\begin{bmatrix} 0.53 \\ 0.48 \end{bmatrix}$ .103±.015  $[2.6 \pm 0.4]$ (4) #26 PIN CONTACT PC TAIL STYLE **WIRE VIEW #26 CONTACT FACE VIEW HEX NUT GASKET** MAT'L: COPPER ALLOY MAT'L: RUBBER, MAT'L: UV PBT, BLACK GOLD PLATED **BLACK** 13/16-27 UNS-2A PANEL CONNECTOR, MALE MODIFIED THREAD MAT'L: UV PBT, BLACK .750 [19.1] W4B81-7PG-3ES  $\emptyset$ .790 [20.1] **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, MA 09-11-24 RELEASED PER PDR 20013-4 AB CREATED PER PDR 20013; P-20013-4 03-19-21 DISCLOSURE, OR USE OF THIS INIT. DATE DESCRIPTION **RECOMMENDED** DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION. PANEL CUT-OUT 03-18-21 SOME! TOLERANCE ±.003 [0.1] 601 E. WILDWOOD VILLA PARK, IL 60181 APPROVED BY: ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. PANEL CONNECTOR KIT
(3) #12 + (4) #26 PIN CONTACTS, PC TAIL DATE: UNLESS OTHERWISE SPECIFIED
TOLERANCES:
3 PLACE DECIMALS ±.005
ANGLES ±1°
FRACTIONS ±1/16 MULTI-CON-X, WEATHER RESISTANT
STOMER: STANDARD PRODUCT SCALE NTS SHEET 1 OF 1 **Rohs Compliant** DIMENSIONS IN BRACKETS [ ] ARE METRIC. FILE: W4B81-7PG-3ES = CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX PART NUMBER: W4B81-7PG-3ES