1. ALL PARTS TO BE BULK PACKED. 3180-2PG-457W 2. RED SILICONE O-RING IS LUBRICATED AND INSTALLED INTO GROOVE OF CABLE CLAMP 3180-3PG-440W 3. CONTACTS SUPPLIED UNASSEMBLED 4. DIMENSIONS ARE REFERENCE ONLY EXCEPT THOSE WITH A TOLERANCE 3180-3PG-450W 3180-3PG-457W .132±.015 3.4±0.4 CONTACT **HEIGHT** (2-3) #12 PIN CONTACTS, CRIMP MAT'L: COPPER ALLOY, GOLD PLATED CUSTOMER PRINT 1.600 .525 1.300 .049 .470 [33] [1.3] [23.7] [[11.9] 40.6 [13.3]**BACKSHELL** CABLE CONNECTOR, MALE CABLE CLAMP MAT'L: UV PBT, BLACK MAT'L: UV PBT, BLACK MAT'L: NYLON, BLACK O-RING GROMMET MAT'L:NEOPRENE, BLACK WINGED COUPLING RING MAT'L: SANTOPRENE, BLACK MAT'L: NYLON, BLACK **FACE VIEW** 3180-XPG-4XXW O-RING MAT'L: SILICONE, RED **DETAIL A** 2.45 MAX [62.2 MAX] **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, MA 04-09-24 1.130 [28.7] PNK 05-19-23 PRR# P-22008-2 DISCLOSURE, OR USE OF THIS REV. INIT. DATE DESCRIPTION DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION. PNK APPROVED BY: SHOWN ASSEMBLED DATE: FOR CUSTOMER REFERENCE ONLY SCALE SIZE NTS B **Rohs Compliant** DIMENSIONS IN BRACKETS [ ] ARE METRIC

 ASSEMBLY P/N
 GROMMET I.D. / CABLE O.D. RANGE
 CONTACTS

 3180-2PG-440W
 0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]
 2 #12

 3180-2PG-450W
 0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]
 2 #12

 3180-2PG-457W
 0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]
 3180-3PG-440W

 3180-3PG-440W
 0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]
 3 #12

 3180-3PG-457W
 0.570 [12.7] / 0.400 - 0.570 [12.7 - 14.5]
 3 #12



