

- FLAT WASHER STEEL, NIĆKEL PLATED SEAL COVER, O-RING - SILICONE, BLACK POTTING COMPOUND - SILICONE ADHESIVE, LIGHT GRAY
- 2. FOR HAND INSERTION USE 0.130 [3.30] SPACING. FOR AUTOMATED INSERTION USE 0.135 [3.43] SPACING.
- 3. IT IS RECOMMENDED THAT THE JACK MOUNTING NUT BE TIGHTENED SNUG BY HAND BEFORE APPLYING A FINAL TIGHTENING TORQUE OF 3-4 LB-IN USING HAND TOOLS ONLY. POWER DRIVER OR IMPACT DRIVERS ARE NOT RECOMMENDED.
- 4. DIMENSIONS SHOWN FOR REFERENCE ONLY.
- 5. THE PRODUCTS IN THIS SERIES ARE ROHS COMPLIANT.



							THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.								
						UNLESS OTHERWISE SPECIFIED	SIZE	W	IDTH MULT			LBS/M		TEMPER	
						1. ALL DIMENSIONS IN INCHES [mm]	FINISH				MATERIAL				
						- TWO PLACE DECIMALS ±0.02 [0.5]	SPEC No.			SPEC No.					
ł						. ,	FIRST USED ON		۱ :	SCALE					•
						- THREE PLACE DECIMALS ±0.005 [0.13]				3:1	Smilehe			~M~~GD~	
							DATE DRAWN	BY	CHKD	APVD					
ł							5/28/24	PNK	PNK	SRC					
	Α	28689	07/16/24	PC	TJK		3/20/24	FINIX	5/28/24	5/28/24		SHEET	1 ()F 1	
	REV	ECO NUMBER	DATE	BY	APVD		NAME			PART No		454		REV	
	REVISIONS					DO NOT SCALE DRAWING	2.1mm POWER JACK, RIGHT-ANGLE PC SEALED UNMATED, RoHS				721RAU A			<u> </u>	

SolidWorks CAD File B