



CUSTOMER PRINT

CA6C806SPXXX90

PART NUMBER:

- FINISHED PRODUCT TO BE COILED
  OVERMOLD BOOT MATERIAL: UV PBT, BLACK
  ELECTRICAL TEST: 100% CONTINUITY
  ALL DIMENSIONS ARE REFERENCE EXCEPT THOSE WITH A TOLERANCE





DIMENSIONS IN BRACKETS [ ] ARE IN MILLIMETERS UNLESS INDICATED

CUSTOMER APPROVAL	_						
THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL							
CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS		MA	08-17-21	DRAWING CREATED PER DOR 21-109361DS-1			
DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY	REV.	INIT.	DATE	DESCRIPTION			
PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.		ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.		ORIG. DRAWN BY: DATE: MA 08-17-21 Checked by:	conxall		
APPROVED BY: DATE:		ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.			601 E. WILDWOOD VILLA PARK, IL 60181		
				APPROVED BY:	TITLE: CABLE ASSEMBLY 2#16/4#20 SKT CONTACTS		
				SCALE SIZE SHEET NTS B 1 OF 1	INSTA-CLICK™ MINI-CON-X MIX SIG BULLET customer: STANDARD PRODUCT		
RoHS COMPLIANT			CHARACTERISTIC SPEC. XXXX	FILE: DIRECTORY: CA6C806SPXXX90 SLW	PART CA6C806SPXXX90		

WIRE COLOR CODE						
POS. 1	POS. 2	POS. 3	POS. 4	POS. 5	POS. 6	
BLK	WHT	RED	BLU	GRN	YEL	
16 AWG	16 AWG	20 AWG	20 AWG	20 AWG	20 AWG	

ASS'Y P/N	"X" DIM
CA6C806SP03990	3 FT. 3 1/2 IN. ±2 IN. [1M ±50.8mm]
CA6C806SP07990	6 FT. 7 IN. ±2 IN. [2M ±50.8mm]
CA6C806SP19790	16 FT. 5 IN. ±4 IN. [5M ±101.6mm]
CA6C806SP39490	32 FT. 9 3/4 IN. ±8 IN. [10M ±203.2mm]
CA6C806SP <u>XXX</u> 90	

CABLE LENGTH IN "INCHES"