

## NOTES:

 $\rightarrow$ 

- 1. DIMENSIONS SHOWN FOR REFERENCE ONLY.
- 2. HEX NUT AND FLAT WASHER SUPPLIED UNASSEMBLED.
- 3. MATERIAL

HOUSING, HEX NUT - COPPER ALLOY, NICKEL PLATED INSULATOR HOUSING - THERMOPLASTIC, RED TERMINAL INSULATORS - PHENOLIC FLAT WASHER - STEEL, NICKEL PLATED PIN, SPRING, TERMINALS - COPPER ALLOY, SILVER PLATED SEAL COVER, O-RING - SILICONE, BLACK POTTING COMPOUND - SILICONE ADHESIVE, LIGHT GRAY

- 4. IT IS RECOMMENDED THAT THE JACK MOUNTING NUT BE TIGHTENED SNUG BY HAND BEFORE APPLYING A FINAL TIGHTENING TORQUE OF 3-4 LB-IN USING HAND TOOLS ONLY. POWER DRIVER OR IMPACT DRIVERS ARE NOT RECOMMENDED.
- 5. THESE PRODUCTS ARE RoHS COMPLIANT

## **CUSTOMER DRAWING**

											OPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED FIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.  LBS/M TEMPER				
					ALL DIMENSIONS IN INCHES [mm]     TWO PLACE DECIMALS ±0.02 [0.5]	FINISH SPEC No.				MATERIAL SPEC No.					
					- THREE PLACE DECIMALS ±0.005 [0.13]	FIRST USED ON		1	SCALE 3:1			75			─────────────────────────────────────
	00000	07/40/04		TIV		5/23/24	BY PNK	CHKD PNK	APVD SRC					∫@∐∐ 	
A	28689	07/16/24	PC	TJK		3/23/24	1 1411	5/23/24	5/23/24		SHEET	1	OF	1	
REV	ECO NUMBER	DATE	BY	APVD		NAME 2.1mm POWER JACKS				PART No					REV.
REVISIONS					DO NOT SCALE DRAWING	SOLDER LUGS, SEALED UNMATED, RoHS				L721AU A				A	

SolidWorks CAD File B