



NOTES:

- MATERIALS:**
 HOUSING - THERMOPLASTIC, BLACK
 SHELL - COPPER ALLOY, NICKEL PLATED
 TERMINALS - COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATED ON SOLDER TAIL
- ELECTRICAL CHARACTERISTICS:**
 CONTACT RESISTANCE - 30m OHMS MAX
 INSULATION RESISTANCE - 1000M OHMS MIN @ 500V DC
 CURRENT RATING - 1.5A MAX
 DIELECTRIC WITHSTANDING - 500V AC FOR 1 MINUTE
- OPERATING TEMPERATURE - 25°C TO +85°C**
- THIS PART IS RoHS COMPLIANT.**

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON			SCALE	
								5:1	
A	28548	10/26/22	PC	TJK	DATE DRAWN	BY	CHKD	APVD	
					8/26/22	MK	10/21/22	10/21/22	
REVISIONS					NAME				
					RIGHT ANGLE USB TYPE-A 2.0, RoHS				
					PART No. RAHPCUA20				
					SHEET 1 OF 1				
					REV A				