



**NOTES:**

1. MATERIALS:  
 HOUSING - THERMOPLASTIC, BLACK  
 TERMINALS - COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATED ON SOLDER TAIL  
 SHELL - COPPER ALLOY, NICKEL PLATED
2. ELECTRICAL CHARACTERISTICS:  
 CONTACT RESISTANCE - 30m OHM MAX  
 INSULATION RESISTANCE - 1000M OHM MIN @ 500V DC  
 CURRENT RATING - 1.0A MAX  
 DIELECTRIC WITHSTAND VOLTAGE - 500V AC FOR 1MINUTE
3. OPERATING TEMPERATURE: -25°C TO +85°C
4. THIS PART IS RoHS COMPLIANT

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE		
					-		3:1		
DATE DRAWN		BY	CHKD	APVD					
8/24/22		TS	TS	TS					
			10/24/22	10/24/22					
					NAME			PART No.	
					RIGHT ANGLE TYPE-B			RAHPCUB20	
					USB 2.0, RoHS			REV	
								A	
REVISIONS					DO NOT SCALE DRAWING				
A	28548	10/26/22	PC	TJK					
REV	ECO NUMBER	DATE	BY	APVD					

SolidWorks CAD File