





- NOTES:
1. PANEL CONNECTORS TO BE PACKED IN PARTITIONED BOX, 100 PC PER BOX.
 2. ALL HOLES REQUIRED REGARDLESS OF NUMBER OF POSITIONS OF CONNECTOR.
 3. HEX NUT AND GASKET SHIPPED UNASSEMBLED
 4. HEX NUT TIGHTENING TORQUE: 9 IN./LB MAX.
 5. CURRENT RATING: 5.0 AMP
 6. TEMPERATURE RATING: -40°C TO +85°C (-40°F TO +185°F)
 7. MATERIALS:
PANEL CONNECTOR, HEX NUT, SPACER: UV PBT
GASKET: RUBBER
CONTACTS: COPPER ALLOY, GOLD PLATED
PCB: FR-4
HEADER INSULATOR: THERMOPLASTIC, UL94V-0
 8. REAR WELL OF PANEL CONNECTOR TO BE FILLED WITH EPOXY.
 9. SEE DRAWING HPMCSTD FOR HOLE PATTERN.
 10. ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE SPECIFIED.





ASS'Y P/N	CONTACT QTY.
W17861-4PG-3ES	4





FACE VIEW




WIRE VIEW



SHOWN ASSEMBLED
FOR CUSTOMER REFERENCE ONLY



4 POSITION LOCATIONS



RECOMMENDED
PANEL CUT-OUT
TOLERANCE: ±.003

CUSTOMER APPROVAL


THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.

APPROVED BY: _____

DATE: _____

DIMENSIONS IN BRACKET [] ARE METRIC.

RoHS COMPLIANT

A	AN	10-31-25	DRAWING RELEASED PER PDR P-21001-4			
	JWM	08-29-25	INITIAL RELEASE PER 21001			
REV.	INIT.	DATE	DESCRIPTION			
D	ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.		ORIG. DRAWN BY:		DATE:	
			AB			08-13-21
	ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.		CHECKED BY:		 601 E. WILDWOOD VILLA PARK, IL 60181	
			APPROVED BY:			
			TITLE:			
= CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX		SCALE		SIZE		SHEET
		NTS		B	1 OF 1	
		FILE:		DIRECTORY:		PART NUMBER:
		W17861-4PG-3ES		SLW		
						W17861-4PG-3ES
						REV A