					CONNECTOR P/N	GROMMET I.D. / CABLE O.D. RANGE	CONTACTS
	NOTEC.				W3382-4SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	
	NOTES:				W3382-4SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	4 #16
	 ALL PARTS ARE BULK PACKED. RED SILICONE O-RING IS LUBRICATED AND 	INSTALLED INTO			W3382-4SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	
	GROOVE OF CABLE CLAMP			W3382-5SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]		
	 CONTACTS ASSEMBLED INTO CONNECTOR ALL DIMENSIONS ARE REFERENCE EXCEPT 				W3382-5SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	5 #16
	THOSE WITH A TOLERANCE				W3382-5SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	
					W3382-6SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	
					W3382-6SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	6 #16
					W3382-6SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	
CUSTOMER PRINT	FACE VIEW W3382-4SG-P-4XX KEYWAY 5 0 0 1 1 2	.044±.015 [1.1±0.4] .935 [23.7] A (4-6) #16 PIN O	1.600 [40.6]	.525	1.300 [33]	WIRE VIE W3382-4SG-P- KEYWAY	3 EW 4 4 4 4
W3382-XSG-P-4XX	FACE VIEW W3382-5SG-P-4XX KEYWAY FACE VIEW W3382-6SG-P-4XX	CABLE CONNECTOR, FEMALE MAT'L: UV PBT, BLACK COUPLING RING MAT'L: UV PBT, BLACK O-RING MAT'L: SILICONE, RED SPRING MAT'L: STAINLESS STEEL 2.46 MAX [62.4 MAX]	CABLE-CLAMP MAT'L: UV PBT, E O-RING- MAT'L: SILICONE, RED	GROMME MAT'L: SA DETAIL A	T ANTOPRENE, BLACK	BACKSHELL MAT'L: UV PBT, BLACK WIRE VIE W3382-5SG-P-2 KEYWAY WIRE VIE W3382-6SG-P	5 6 4
PART W3	1.099 [27.9]	SHOWN ASSEMBLED FOR CUSTOMER REFERENCE ONLY DIMENSIONS IN BRACKS	ETS [] ARE IN MILLIMETERS U	INFORMATION PRO CORPORATION. A DISCLOSURE, DOCUMENT /INFOR PROHIBITED UNL WRITING BY CON APPROVED BY: DATE:	ONTAINS CONFIDENTIAL PRIETARY TO CONXALL ANY REPRODUCTION, OR USE OF THIS MATION IS EXPRESSLY ESS AUTHORIZED IN IXALL CORPORATION.	MA 07-31-25 UPDATED MANUFACTURING DRAWING PER E MA 04-23-24 RELEASED PER PDR 22008-2 PNK 7-28-23 CUSTOMER DRAWING I. INIT. DATE LINFORMATION LILUSTRATED IS THE PROPIETY OF "CONVALI OPERATION" INAUTHORIZED PULCATION OF DISTRIBUTION OF PULCATION OF DISTRIBUTION OF PLICATION OF INCHES AND DECIMALS. ALL UNITS ARE IN FEET, NCHES, FRACTION OF INCHES AND DECIMALS. APPROVED BY: TITLE: CABLE COI (4-6) #16 SOCKET INSTA-CLIC SCALE SIZE SHEET NTS R 1 OF 1 CUSTOMERS STANDARE	CCR 9829 D VILLA PARK, IL 60181 NNECTOR ASS'Y I CONTACTS, SOLDER K™ MULTI-CON-X D PRODUCT