















- NOTES:
- 1. ALL PARTS TO BE BULK PACKED.
 - 2. RED SILICONE O-RING IS LUBRICATED AND INSTALLED INTO GROOVE OF CABLE CLAMP
 - 3. CONTACTS SHIPPED UNASSEMBLED
 - 4. DIMENSIONS ARE REFERENCE ONLY EXCEPT THOSE WITH A TOLERANCE



ASSEMBLY P/N	GROMMET I.D. / CABLE O.D. RANGE	CONTACTS
W5280-4SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	4 #20
W5280-5SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	5 #20
W5280-6SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	6 #20
W5280-6SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	
W5280-6SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	7 #20
W5280-7SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	
W5280-7SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	
W5280-7SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	8 #20
W5280-8SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	
W5280-8SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	
W5280-8SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	9 #20
W5280-9SG-P-440	0.400 [10.2] / 0.320 - 0.400 [8.1 - 10.2]	
W5280-9SG-P-450	0.500 [12.7] / 0.400 - 0.500 [10.2 - 12.7]	
W5280-9SG-P-457	0.570 [14.5] / 0.500 - 0.570 [12.7 - 14.5]	



CUSTOMER APPROVAL

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.

APPROVED BY: _____

DATE: _____

A	MA	05-16-24	RELEASED PER PDR 22008-5	
	PNK	06-02-23	PRR# P-22008-5	
REV.	INIT.	DATE	DESCRIPTION	
			ORIG. DRAWN BY: PNK	DATE: 06-02-23
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			CHECKED BY:	 601 E. WILDWOOD VILLA PARK, IL 60181
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.			APPROVED BY:	
= CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX			SCALE: NTS	
FILE:	W5280-XSG-P-4XX	DIRECTORY:	SLW	PART NUMBER: W5280-XSG-P-4XX
TITLE: INLINE CONNECTOR ASS'Y (4-9) #20 SOCKET CONTACTS, CRIMP INSTA-CLICK™ MULTI-CON-X STANDARD PRODUCT				REV A