



NEW PRODUCT BULLETIN 682

DIN 1.0/2.3 CONNECTORS



Switchcraft[®]
CONXALL[®]

HARSH ENVIRONMENT CONNECTIVITY SOLUTIONS

5555 N ELSTON AVE | CHICAGO, IL | 773.792.2700 | SALES@SWITCHCRAFT.COM | WWW.SWITCHCRAFT.COM



Compatible with widely used cable sizes with a 75 Ohm rating

Built with high quality copper alloy, gold-plated contacts

DIN 1.0/2.3

SWITCHCRAFT'S DIN 1.0/2.3 utilize a unique push/pull lock and release feature, simplifying installation and modification. They are 75 Ohm rated, compatible with the most widely used cable sizes, and can be terminated using a standard BNC crimp tool.



75 OHM RATED

75 Ohm rated with compatibility with most cable sizes



12 GHz

UHD version rated at 12 GHz for Ultra High Definition video



**SWITCHCRAFT®
QUALITY**

Switchcraft connectors are built with the highest quality material

PART NO.	DESCRIPTION
DIN1505A	DIN 1.0/2.3 Connector for Belden #1505A
DIN1694A	DIN 1.0/2.3 Connector for Belden #1694A
DIN1855A	DIN 1.0/2.3 Connector for Belden #1855A
DIN1855ENH	DIN 1.0/2.3 Connector for Belden #1855ENH
DINFT	DIN 1.0/2.3 Feed-thru Connector
UHDDIN05	UHD DIN 1.0/2.3 Plug, 4505R
UHDDIN55	UHD DIN 1.0/2.3 Plug, 4855R
UHDDIN94	UHD DIN 1.0/2.3 Plug, 4694R